

# GAS FURNACES

80% | 95% | 96%



When the weather gets chilly, you'll get comfortable, consistent heating—and you can also be confident these furnaces are built for durable performance over the long haul.



## 80% SINGLE STAGE UPFLOW HORIZONTAL

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J801P045AU3SAA	80%	45,000	Upflow/Horizontal Right/Left	34.5 x 14.5 x 28
J801P054AU3SAA	80%	54,000	Upflow/Horizontal Right/Left	34.5 x 14.5 x 28
J801P072BU4SAA	80%	72,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J801P072CU5SAA	80%	72,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801P090BU4SAA	80%	90,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J801P090CU5SAA	80%	90,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801P108CU5SAA	80%	108,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801P126DU5SAA	80%	126,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

## 80% SINGLE STAGE DOWNFLOW

J801P054AD3SAA	80%	54,000	Downflow	34.5 x 14.5 x 28
J801P072BD4SAA	80%	72,000	Downflow	34.5 x 17.5 x 28
J801P090BD4SAA	80%	90,000	Downflow	34.5 x 17.5 x 28
J801P108CD5SAA	80%	108,000	Downflow	34.5 x 21 x 28
J801P126DD5SAA	80%	126,000	Downflow	34.5 x 24.5 x 28

SEE PAGE 2 FOR SPECIFICATIONS ON THE 95% & 96% FURNACE

- ▶ All furnace models feature a standard silicon nitride igniter.
- ▶ Furnace models feature aluminized steel heat exchangers to conduct heat quickly and increase durability.
- ▶ Oxbox furnaces are built for flexibility to suit varied installations.
- ▶ Furnaces are fully convertible to either natural gas or propane, making them suitable for use in any area.
- ▶ Galvanized steel cabinets resist corrosion.



# GAS FURNACES

80% | 95% | 96%



## 95% SINGLE STAGE UPFLOW HORIZONTAL

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J951P038BU4SAA	95%	38,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J951P054BU4SAA	95%	54,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J951P072CU5SAA	95%	72,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J951P090CU5SAA	95%	90,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J951P108DU5SAA	95%	108,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28
J951P120DU5SAA	95%	120,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

## 95% SINGLE STAGE DOWNFLOW

J951P054BD4SAA	95%	54,000	Downflow	34.5 x 17.5 x 28
J951P072CD5SAA	95%	72,000	Downflow	34.5 x 21 x 28
J951P090CD5SAA	95%	90,000	Downflow	34.5 x 21 x 28
J951P118DD5SAA	95%	118,000	Downflow	34.5 x 24.5 x 28

## 95% 2-STAGE VARIABLE SPEED UPFLOW HORIZONTAL

J952E060BUVSAA	95%	60,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J952E080CUVSAA	95%	80,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J952E100CUVSAA	95%	100,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J952E120DUVSAA	95%	120,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

Our innovative 1-5-10 no-registration warranty gives you maximum peace of mind. Plus, every piece of equipment is warranted to the home, not the homeowner—providing an extra measure of coverage when it comes time to sell.

### WARRANTIES AVAILABLE:

- ▶ **1 Year: Complete Replacement**  
ONLY COMPRESSORS, COILS, OR HEAT EXCHANGER FAILURE
- ▶ **5 Years: Standard Parts Warranty**
- ▶ **10 Years: Compressor Replacement**

## 96% 2-STAGE VARIABLE SPEED DOWNFLOW

J962E060BDVSAA	96%	60,000	Downflow	34.5 x 17.5 x 28
J962E080CDVSAA	96%	80,000	Downflow	34.5 x 17.5 x 28
J962E100CDVSAA	96%	100,000	Downflow	34.5 x 17.5 x 28
J962E115DDVSAA	96%	115,000	Downflow	34.5 x 17.5 x 28

For installation in SCAQMD only: These furnaces do not meet the SCAQMD Rule 1111 14 ng/J NOx emission limit and are only eligible for installation in high altitude (4,200 feet and above) or propane applications and are subject to a mitigation fee of up to \$450 USD. This furnace is not eligible for the Clean Air Furnace Rebate Program: [www.CleanAirFurnaceRebate.com](http://www.CleanAirFurnaceRebate.com)

**Questions?** Go to [OXBOXHVAC.COM](http://OXBOXHVAC.COM) for more information.

